


# Citrus Foaming Degreaser

Foaming Degreaser



Specifications

Citrus Foaming Degreaser



## DESCRIPTION

**Hercules Citrus Foaming Degreaser** applies a foam that emulsifies and washes away grease and dirt. Use on all heating, air conditioning and refrigeration equipment. Ideal for hard to reach places. This product is non-corrosive and contains no petroleum distillates, caustics or phenols. Effectively deodorizes as it cleans. **Citrus Foaming Degreaser** is safe on most plastics, cements and metal surfaces. Provides effective removal of oil-based grease, tar, grime, slime, and carbon from strainers, compressors and other heating, air conditioning and refrigeration parts.


Contains no CFC's and is non-chlorinated.

## SIZES AND PACKING

STOCK NO.	SIZE	PACKING	WEIGHT/CASE
35-185	17 oz.	12	16.6 lbs.

# Citrus Foaming Degreaser

## Foaming Degreaser



### APPROVALS AND LISTINGS

Not applicable.

### SPECIFIC USES

Use **Hercules Citrus Foaming Degreaser** to remove grease, oil and dirt quickly and efficiently.

### SPECIFIC APPLICATIONS\*

Apply **Hercules Citrus Foaming Degreaser** to remove grease, grime, oil, dirt from any metal or hard surfaces including fuel oil trucks and concrete driveways, burner parts, strainers, compressors and other heating and refrigeration equipment.

### PHYSICAL PROPERTIES

Specific Gravity	.908
Solubility in water:	Complete
Boiling Point (°F):	212°F
Vapor Pressure:	35 psig @ 70°F
Appearance and color:	White emulsion liquid with fresh orange odor.

### WARNINGS OR CAUTIONS

- **FLAMMABLE.** Do not store near fire, heated surfaces, sparks, or flames.
- Read all cautions and directions carefully before using this product.
- Avoid contact with eyes and skin.
- Use in well ventilated areas. Intentional misuse of aerosol products by inhaling concentrated vapors may be harmful or fatal.
- Dispose of can in accordance with Federal, State and local regulations.
- Contents under pressure. Do not store at temperatures over 120°F.
- Do not puncture or incinerate can.
- May affect painted surfaces. Test in small area before applying.

### DIRECTIONS FOR USE

SHAKE WELL BEFORE USING. Protect areas that are not being degreased from spray or drippings. Hold can 6 to 8 inches from surface. Spray sparingly and wipe clean with soft cloth after allowing time to penetrate grease. For heavy grease or oil deposits wipe with cloth or brush to work degreaser into soiled areas. Allow to penetrate for 10 minutes or more. Flush area thoroughly with hot water or steam. May affect painted areas. Test in small area before applying.

### MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST MATERIAL SAFETY DATA SHEET (MSDS) #101

For Delivery by Fax	Call 1-800-942-4636
Internet	See MSDS section of <a href="http://www.herchem.com">www.herchem.com</a>
Mail	Contact Hercules at address below or any Hercules representative

HMIS Hazard warning 1-3-0-G.

INGREDIENTS	CAS#
Isobutane	75-28-5
Propane	74-98-6
D-Limonene	5989-27-5

\* For special applications which may not be covered on this or other Hercules literature, please contact Hercules Technical Services Department by phone at 1-800-221-9330 or send a fax to 1-800-333-3456.



**HERCULES®** <http://www.herchem.com>

### Hercules Chemical Company, Inc.

111 South Street, Passaic, NJ 07055-9100  
Phone: 800-221-9330 • Fax: 800-333-3456  
e-mail: [info@herchem.com](mailto:info@herchem.com)

